



## Application Guidelines

- Eliminate all visible mold from the surface
- Rinse with water
- Apply Vital Oxide from a distance of 12 inches until visibly wet.
- Application may be done with a spray bottle or a fogging device.
- Allow ventilation to air dry

## Coverage

Coverage are varies because of surface type and application method.

- 32oz covers 2000 sq.ft.
- 128oz (1 gal) 8000 sq. ft.

## Product Specifications

Appearance:.....Colorless liquid  
 Physical State:.....Liquid  
 Boiling Point (°F):.....212  
 Freezing Point (°F):.....32  
 Volatile Organic Compounds (VOC):.....None  
 Specific Gravity:.....1.003 @ 68°F (20°C)

Odor:.....Mild-Fresh, Ozone like  
 pH:.....8 - 9  
 Solubility in Water:.....100%  
 Vapor Pressure (mm Hg):.....Not Available  
 Evaporation Rate:.....Less than Ether  
 Density (lb/gal):.....8.40 @ 68°F (20°C)

## HMIS Rating:

Health: 0      Flammability: 0      Reactivity: 0      PPE: None

## Potential Health Effects

**Eye Contact:** Eye contact may cause mild eye irritation with discomfort.

**Skin Contact:** Does NOT cause skin irritation and the product is NOT skin sensitizer.

**Inhalation:** Does NOT cause any respiratory irritation. If consumer product accidentally contacts strong acids in restricted ventilation area, avoid breathing the vapors and allow adequate time for the vapors to disperse before re-entering the restricted area.

**Ingestion:** Non-Toxic